



### **COUNTER MOUNT ADJUSTABLE COLLAR CUP DISPENSERS**

C Series Counter Mount dispensers come with adjustable collars to accommodate a specific range of cup sizes. Durable 26 gauge stainless steel construction gives exceptional long term performance, and the dispensers are available in Vertical, Horizontal or Foam cup models to suit demanding installations.

Many busy fast food outlets enjoy the reliability and good looks of these models.

#### **C3400 SERIES**

FOR CUP RIM DIAMETERS **70-98MM** Tube length 597mm, Counter hole dia. 119mm)

CODE	MOUNT	CUP TYPE	APPROX. CUP SIZE
C3400CH	Horizontal	Paper/plastic	350-710ml

### **C3500 SERIES**

FOR CUP RIM DIAMETERS 101-123MM

Tube length 597mm, Counter hole dia. 146mm)


CODE	MOUNT	CUP TYPE	APPROX. CUP SIZE
C3500CH	Horizontal	paper/plastic	950-1360ml






### **C SERIES INSTRUCTIONS**


# **INSTALLATION**



**Cut hole size** for desired dispenser. To determine proper hole diameter refer to specifications.



Fasten mounting ring securely over hole with the supplied mounting hardware.



Place dispenser into hole. Align ear tabs on dispenser to openings on mounting ring. Rotate dispenser one quarter turn clockwise to secure to counter.

NOTE: This unit is self supported by mounting ring. No additional support is needed when mounting in a horizontal position.

### **ADJUSTMENT**



Remove dispenser from counter by rotating counterclockwise and pulling from hole.



Loosen locking screw, and load cups into dispenser.




Turn collar counterclockwise until adjustment clips hold cups firmly in place. Tighten locking screw. DO NOT BEND CLIPS BY HAND!

NOTE: For proper operation, cups should dispense from middle of adjustment clips.

## **MAINTENANCE**



Remove spring assembly by rotating plastic base clockwise until tabs are released from Pull bottom out window. carefully.



Remove spring and cup holder., Wash all parts with warm soapy water to remove dirt and wax build up. Do not bend the adjustment clips by hand.



Reassemble unit by inserting cup holder, spring and bottom, making sure tabs snap into Be sure to check windows. adjustment before reinstalling.