

IMC's VQ Peelers are the perfect potato peeling solution for smaller catering establishments.

The VQ Peelers have been designed and built to withstand repeated, long-term use, capable of providing years of reliable performance.

Their compact and flexible design, small footprint and quiet running motor enable them to be used in the smallest of kitchens whilst their simple and safe operation make them a pleasure to use.

VQ Peelers are available with a capacity of 3.5kg or 7kg.



VQ3.5 MODEL - CAPACITY 3.5KG

Includes timer function, suitable for up to 80kg /hr
240V 180W supplied with 10a plug




VQ7 MODEL - CAPACITY 7KG

Includes timer function, suitable for up to 150kg /hr
240V 180W supplied with 10a plug


Accessories include sink skip, small peel trap and waste ejector - call for further details

SPECIFICATIONS IMC VQ SERIES PEELERS



VQ 3.5

General	
Mounting	Worktop-, drainer-, stand- or pedestal-mounted
Capacity	3.5kg (7lb)
Output	35kg/hour
Dimensions (h x w x d)	425mm x 650mm max x 380mm
Discharge height	170mm
Discharge heights with pedestal	750, 800, 850, 900 and 950mm
Discharge height with trolley	1055mm
Electrical information	
Motor	180W 230-1-50/60
Installation information	
General	A level table or sink-top
Water connection	WRAS approved water inlet hose and air break supplied Connect to an adjacent cold water supply
Waste water outlet connection	250mm long 54mm diameter flexible rubber waste pipe
Electrical connection	2.5m mains cable supplied with 10A plug for single phase
Customer accessories	
	E72/011 Sink skip - stainless steel
	S72/220 Trolley
	S72/221 Pedestal - adjustable height
	S72/023 Waste ejector for more effective waste evacuation
	S58/569 Interceptor tank
	A29/003 Lid retaining strap
Shipping specification	
Packing dimensions (h x w x d)	455mm x 730mm x 420mm
Packing volume	0.140m ³
Packing weight (gross/net)	31/27kg



VQ 7

General	
Mounting	Worktop-, drainer-, stand- or pedestal-mounted
Capacity	7kg (14lb)
Output	50kg/hour
Dimensions (h x w x d)	500mm x 650mm max x 380mm
Discharge height	170mm
Discharge heights with pedestal	750, 800, 850, 900 and 950mm
Discharge height with trolley	1055mm
Electrical information	
Motor	180W
Voltages	230-1-50/60
Installation information	
General	A level table or sink-top
Water connection	WRAS approved water inlet hose and air break supplied Connect to an adjacent cold water supply
Waste water outlet connection	250mm long 54mm diameter flexible rubber waste pipe
Electrical connection	2.5m mains cable supplied with 10A plug for single phase
Customer accessories	
	E72/011 Sink skip - stainless steel
	S72/220 Trolley
	S72/221 Pedestal - adjustable height
	S72/023 Waste ejector for more effective waste evacuation
	S58/569 Interceptor tank
	A29/003 Lid retaining strap
Shipping specification	
Packing dimensions (h x w x d)	530mm x 730mm x 420mm
Packing volume	0.163m ³
Packing weight (gross/net)	33/29kg

Capacities are approximate and output may vary depending on the type and age of potatoes used.
All diagram dimensions are in mm.

FSM (FOOD SERVICE MACHINERY PTY. LTD.)
HEAD OFFICE: UNIT E6, 63-85 TURNER STREET,
 PORT MELBOURNE, VIC. 3207 AUSTRALIA
 T: +61 3 8645 2555 F: +61 3 8645 2565
 E: sales@fsm-pl.com.au W: www.fsm-pl.com.au

SYDNEY OFFICE:
 UNIT 15, 7-9 PROGRESS CIRCUIT,
 PRESTONS, NSW 2170 AUSTRALIA
 T: +61 2 9608 8620 F: +61 2 9607 9370
 E: sales@fsm-pl.com.au W: www.fsm-pl.com.au

QUEENSLAND:
 T: 0400 099 992
 E: sales@fsm-pl.com.au
 W: www.fsm-pl.com.au