

FSM U Series Under Counter models offer versatile dual function with one door chiller and one door freezer compartments in the one unit. Ideal where space is at a premium, with convenient digital controls, magnetic door closers and proven high performance.

DUAL UNDER COUNTER CHILLER & FREEZER

- ▶ High density polyurethane foam insulation.
- ▶ Stainless Steel exterior and interior.
- ▶ Magnetic closing doors with large ergonomic handles
- ▶ Insulated partition between left freezer and right chiller for temperature integrity
- ▶ High output fan cooling system.
- ▶ Auto-defrosting and digital controller.
- ▶ Self-evaporating drainage system.
- ▶ Door gaskets are easily replaceable.
- ▶ Durable PVC coated shelves and internal round corner edges for easy cleaning.
- ▶ Chiller temp range: +2°C to +5°C.
- ▶ Freezer temp range: -10°C to -18°C.
- ▶ Ambient temperature rated 36°C.
- ▶ Supplied on 100mm dia. castors with 10amp plug.



MODEL	DIMENSIONS EXTERNAL (mm)	DIMENSIONS INTERNAL (mm)	GROSS VOLUME	REFRIGERANT	TEMP RANGE °C	COMPRESSOR	VOLTAGE/AMPS	NET WEIGHT	GROSS WEIGHT	TEMP CONTROL	No. SHELVES
DCF1200SD	1200 x 760 x 840	324 x 635 x 584 CHILLER 324 x 635 x 584 FREEZER	120L 120L	R404A 440g R404A 440g	+1to+5 -10 to -18	1/4HP	240V 4A	88 Kg	120 Kg	DIGITAL	4

UNDER COUNTER FREEZER

- ▶ High density polyurethane foam insulation.
- ▶ Stainless Steel exterior and interior.
- ▶ Magnetic closing doors with large ergonomic handles
- ▶ High output fan cooling system.
- ▶ Auto-defrosting and digital controller.
- ▶ Self-evaporating drainage system.
- ▶ Door gaskets are easily replaceable.
- ▶ Durable PVC coated shelves and internal round corner edges for easy cleaning.
- ▶ Freezer temp range: -10°C to -18°C.
- ▶ 404A Refrigerant.
- ▶ Ambient temperature rated 36°C.
- ▶ Supplied on 100mm dia. castors with 10amp plug.



MODEL	DIMENSIONS EXTERNAL (mm)	DIMENSIONS INTERNAL (mm)	GROSS VOLUME	REFRIGERANT	TEMP RANGE °C	COMPRESSOR	WATTS/AMPS	NET WEIGHT	GROSS WEIGHT	TEMP CONTROL	No. SHELVES
CF1200SD	1200 x 760 x 840	750x 635 x 584	278L	R404A 440g	-10 to -18	1/4HP	600W 4A	88 Kg	120 Kg	DIGITAL	4

HEAD OFFICE:

SYDNEY OFFICE:

QUEENSLAND OFFICE:

PERTH: