



TOP VIEW



FRONT VIEW
NTS



SIDE VIEW

STANDARD FEATURES

- Uniform heat distribution with blanket-type element
- Built-in adjustable thermostat controls surface temperature
- Available in widths from 610 - 1372 mm and 495mm depths
- Extruded aluminum base with stainless steel top
- Standard legs: 25mm rubber
- All models include a 1829 mm cord and plug attached

Hatco's **Glo-Ray Heated Shelf** has an extruded aluminum base with non-slip rubber feet, stainless steel top and blanket-type element for uniform heat distribution. Fiberglass insulation keeps heat at the holding surface while a built-in adjustable thermostat controls surface.

SPECIFICATIONS

Model	Dimension	Ship Weight	Voltage	Phase	Watts	Amps	Plug
GRS-24-I	610 mm W x 495 mmD	10kg	120	Single	380	3.2	NEMA 5-15P
GRS-30-I	762 mm W x 495 mmD	12kg	120	Single	490	4.0	NEMA 5-15P
GRS-36-I	914 mm W x 495 mmD	13kg	120	Single	598	5.0	NEMA 5-15P
GRS-42-I	1067 mm W x 495 mmD	15kg	120	Single	652	5.4	NEMA 5-15P
GRS-48-I	1219 mm W x 495 mmD	17kg	120	Single	760	6.3	NEMA 5-15P
GRS-54-I	1372 mm W x 495 mmD	20kg	120	Single	870	7.25	NEMA 5-15P